

INTERNATIONAL A-LEVEL MATHEMATICS

MA05

(9660/MA05) Unit M2 Mechanics

Mark scheme

January 2020

Version: 1.0 Final

Mark schemes are prepared by the Lead Assessment Writer and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation events which all associates participate in and is the scheme which was used by them in this examination. The standardisation process ensures that the mark scheme covers the students' responses to questions and that every associate understands and applies it in the same correct way. As preparation for standardisation each associate analyses a number of students' scripts. Alternative answers not already covered by the mark scheme are discussed and legislated for. If, after the standardisation process, associates encounter unusual answers which have not been raised they are required to refer these to the Lead Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of students' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this mark scheme are available from oxfordaqaexams.org.uk

Copyright information

OxfordAQA retains the copyright on all its publications. However, registered schools/colleges for OxfordAQA are permitted to copy material from this booklet for their own internal use, with the following important exception: OxfordAQA cannot give permission to schools/colleges to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Copyright © 2020 Oxford International AQA Examinations and its licensors. All rights reserved.

Key to mark scheme abbreviations

	Μ	Mark is for method				
	m	Mark is dependent on one or more M marks and is for method				
	Α	Mark is dependent on M or m marks and is for accuracy				
	В	Mark is independent of M or m marks and is for method and accuracy				
	E	Mark is for explanation				
\checkmark	`or ft	Follow through from previous incorrect result				
	CAO	Correct answer only				
	CSO	Correct solution only				
	AWFW	Anything which falls within				
	AWRT	Anything which rounds to				
	ACF	Any correct form				
	AG	Answer given				
	SC	Special case				
	oe	Or equivalent				
	A2, 1	2 or 1 (or 0) accuracy marks				
	– <i>x</i> EE	Deduct <i>x</i> marks for each error				
	NMS	No method shown				
	PI	Possibly implied				
	SCA	Substantially correct approach				
	sf	Significant figure(s)				
	dp	Decimal place(s)				

Q	Answer	Marks	Comments
1(a)	$\mathbf{v} = \begin{bmatrix} 6\cos\left(3 \times \frac{2\pi}{3}\right) \\ 2 - 8\sin\left(4 \times \frac{2\pi}{3}\right) \\ 2 \times \frac{2\pi}{3} + 4e^{-2 \times \frac{2\pi}{3}} \end{bmatrix}$	М1	PI, OE, condone poor use of brackets
	$ \mathbf{v} = \sqrt{\frac{(6\cos(2\pi))^2 + \left(2 - 8\sin\left(\frac{8\pi}{3}\right)\right)^2}{+ \left(\frac{4\pi}{3} + 4e^{-\frac{4\pi}{3}}\right)^2}}$	M1	PI, OE, explicit calculation of the magnitude of their vector (all three components non-zero)
	$ \mathbf{v} = 8.9 \text{ m s}^{-1}$	A1	8.85 m s^{-1} to 3 sf. Condone lack of units
1(b)	$\mathbf{r} = \begin{bmatrix} 2\sin(3t) \\ 2t + 2\cos(4t) \\ t^2 - 2e^{-2t} \end{bmatrix} + \mathbf{c}$	M1 A1	M1: At least one correct component A1: All 3 components correct (Condone lack of +c)
	When $t = 0, r = \begin{bmatrix} 4 \\ 5 \\ 3 \end{bmatrix}$	m1	Use of $+c$ and initial condition (c not the zero vector)
	$\mathbf{c} = \begin{bmatrix} 4\\3\\5 \end{bmatrix}$	A1	OE, Correct vector
	$\mathbf{r} = \begin{bmatrix} 2\sin(3t) + 4\\ 2t + 2\cos(4t) + 3\\ t^2 - 2e^{-2t} + 5 \end{bmatrix}$	A1	OE stated as final answer, CAO
1(c)	$\mathbf{a} = \begin{bmatrix} -18\sin(3t) \\ -32\cos(4t) \\ 2 - 8e^{-2t} \end{bmatrix}$	M1 A1	M1: At least one correct component A1: All 3 components correct
	$\mathbf{a} = \begin{bmatrix} 0\\ -32\\ -6 \end{bmatrix} \text{or} \mathbf{F} = 7.5 \begin{bmatrix} -18\sin(3t)\\ -32\cos(4t)\\ 2-8e^{-2t} \end{bmatrix}$	A1F	Their acceleration vector evaluated at $t = 0$ or their resultant force vector
	$\mathbf{F} = \begin{bmatrix} 0\\ -240\\ -45 \end{bmatrix}$	A1	CAO, OE stated as sole final answer Final answer of 244 N is A0
	Total	12	

Q	Answer	Marks	Comments
			1
2(a)	Vertically component of velocity is initially zero, so $h = \frac{1}{2}gt^{2}$	М1	Explicit use of $s = ut + \frac{1}{2}at^2$ with $u = 0$
	[Time to fall to the ground] $t = \sqrt{\frac{2h}{g}}$	A1	
	$x = ut$ $x = u \times \sqrt{\frac{2h}{g}}$	A1	Use of $s = ut + \frac{1}{2}at^2$ with $a = 0$ or explanation that there is no horizontal acceleration AG
2(b)	[Vertical component of velocity immediately before hitting the ground] $V^2 = 2gh$	M1	Use of $v^2 = u^2 + 2as$ with $u = 0$ Use of $v^2 = u^2 + 2as$ with $u = v$ scores 0/3 PI
	Speed ² of particle immediately before hitting the ground $u^2 + V^2 = u^2 + 2gh$	m1	PI
	Kinetic energy of particle immediately before hitting the ground $E_K = \frac{1}{2}mu^2 + mgh$	A1	OE, stated as final answer
2(c)	The particle will do work against air resistance, which will decrease the final kinetic energy	E1	An explanation must be given, not simply 'air resistance'
	Total	7	

Q	Answer	Marks	Comments
			•
3(a)	Reaction Friction	B1	Must have clear labels of the three forces near the arrows Do not accept symbols (N, W, mg etc) as labels unless the labels are defined elsewhere
	Weight		Do not accept 'gravity' in place of 'weight'
3(b)	Component of weight down the slope = $12 \times 9.8 \sin(35^{\circ})$ = 67.4[526] N	B1	AWRT 67 N (PI)
	Normal reaction force on block = 12 × 9.8 cos(35°) = 96.3[323] N	М1	AWRT 96 N (PI)
	Friction on block = 0.65 × 96.3323 = 62.6[160] N	A1	
	Resultant force = 67.4526 – 62.6160 = 4.8[4] N down the slope	A1F	FT their friction AWRT 4.8 N Condone lack of direction
3(c)	[Resultant force parallel to the slope = 0] $12 \times 9.8 \sin(\theta) = 0.65 \times 12 \times 9.8 \cos(\theta)$	M1	PI, either side correct
	$\tan(\theta) = 0.65$	m1	Forms an equation in $tan(\theta)$
	$\theta = \tan^{-1}(0.65)$	Δ1	
	$\theta = 33.0^{\circ}$		
	Total	8	

Q	Answer	Marks	Comments
4(a)	The logo is symmetric in the line <i>AB</i>	E1	Any mention of symmetry or that both centres of mass of the two circles lie on <i>AB</i>
4(b)	C.O.M. of complete larger circle is <i>R</i> from <i>B</i>	B1	PI
	[Use of the C.O.M. of circular hole is] $2R - r$ [from <i>B</i>]	B1	PI
	$\rho \pi (R^2 - r^2) \overline{Y} = \rho \pi R^2 \times R$ $-\rho \pi r^2 \times (2R - r)$	M1 m1	M1 : At least one correct term m1 : At least two correct terms (unsimplified or better) Condone lack of ρ
	$[\bar{Y} =] \frac{R^3 - 2Rr^2 + r^3}{R^2 - r^2}$	A1	ISW, ACF, e.g. $[\overline{Y} =] \frac{R^2 + Rr - r^2}{R + r}$ or $R - \frac{r^2}{R + r}$
	Total	6	

Q	Answer	Marks	Comments
	1		
	[Anticlockwise moment about <i>B</i> (or <i>A</i>)]		OE
5(a)	0.4 × 40 × 9.8 = 156.8 N m	B1	Condone use of 9.81 for g leading to 156.96 N m
	[Clockwise moment about <i>B</i> (or <i>A</i>) due to child's weight]	B1	OE Condone use of 9.81 for g leading to
	0.85 × 25 × 9.8 = 208.25 N m		208.4625 N m
	As 208.25 > 156.8, the diving board tips	E1F	Dependent on comparison of their two moment calculations
5(b)	[Clockwise moment about <i>B</i> due to child's weight]	M1	
	0.85 × <i>m</i> × 9.8 or 8.33 <i>m</i>		
	156.8 = 8.33 <i>m</i>		
	<i>m</i> = 18.8	A1	Stated as final answer Condone inclusion of units
5(c)	Make the distance between <i>B</i> and the end of the diving board shorter	E1	Any plausible statement
	This will decrease the clockwise moment a weight would have at the right-hand end of the diving board	E1	Corresponding plausible reason, dependent on previous E1 having been awarded
	Total	7	

Q	Answer	Marks	Comments
6(a)	$\frac{180\ 000}{36} - c \times \sqrt{36} = 250 \times 5.0$	M1 m1	Use of driving force = P/v Finding the correct resultant force (LHS) in terms of c
		A1	Setting the correct resultant force equal to <i>ma</i>
	c = 625	A1	
6(b)	$F - 625 \times \sqrt{25} - 250 \times 9.8 \times \sin(6.0^\circ) = 0$ [$F = 3381$ N]	M1 A1	 M1: Use of resultant force = 0. Condone lack of component of weight for M1 A1: Correct equation
	$P = 3381 \times 25 = 84527 \text{ W}$	M1	Their driving force multiplied by 25
	P = 85 kW	A1	CAO in kW and to 2 sf
	Total	8	

Q	Answer	Marks	Comments
7(a)(i)	$L\cos(40^\circ) = mg$ or W	M1	Use of vertical equilibrium
	$L = \frac{12000 \times 9.8}{\cos(40^{\circ})}$ $L = 1.535 \times 10^{5}$ $L = 1.54 \times 10^{5}$	A1	AG Value of L shown to more than 3 sf or correct unsimplified equation for L (with L as subject)
7(a)(ii)	The lift force is perpendicular to the velocity of the aeroplane	E1	
7(b)	$L\sin(40^\circ) = mr\omega^2$	M1	PI, use of resultant force formula for circular motion
	$\omega^{2} = \frac{1.54 \times 10^{5} \times \sin(40^{\circ})}{12000 \times 2.7 \times 10^{3}}$	m1	0.003055 or 0.0030456 if exact value from (a)(i) used
	$\omega = 0.0553 \text{ [rad s}^{-1}\text{]}$	A1	0.0552 [rad s ⁻¹] if exact value from (a)(i) used
7(c)(i)	[i component directly proportional to] cos(0.0553 t)	B1F	FT their ω from (b)
	[j component directly proportional to] sin(0.0553 t)	B1F	FT their ω from (b)
	$[r =]2700 \cos(0.0553 t) i$ + 2700 sin(0.0553 t) j	B1	CAO, accept 2.7 [km] as coefficients
7(c)(ii)	$[v =] - 149 \sin(0.0553 t) i$ + 149 cos(0.0553 t) j	M1	PI, allow unsimplified FT on (c)(i)
	$[a =] - 8.26 \cos(0.0553 t) i$ - 8.26 sin(0.0553 t) j	A1F	AWFW [-8.2 , -8.3] for coefficients Accept AWFW [-0.0082 , -0.0083] for coefficients [in km s ⁻²]
	Total	11	

Q	Answer	Marks	Comments
8(a)	[Change in GPE of the cart and driver between the start and finish lines] = 120 × 9.8 × 150 = 176 400 J	B1	PI
	[Total energy of the cart and driver at the start line] = $176\ 400 + \frac{1}{2} \times 120 \times 8.0^2$ = $180\ 240\ J$	M1 A1	M1 : Initial KE (3 840 J) A1 : Total Energy (180 240 J)
	[By the conservation of energy] $\frac{1}{2} \times 120 \times v^2 = 180\ 240$	A1	AWRT 55 m s ⁻¹ , accept $2\sqrt{751}$ Condone missing units
	$v = 55 \text{ m s}^{-1}$		SC1 for answer of 54.2 m s ⁻¹ [initial KE not included]
8(b)(i)	[Kinetic energy of cart and driver at the finish line] = $\frac{1}{2} \times 120 \times 30^2$ = 54 000 J	B1	PI
	[Total work done by the cart and driver against the resistive forces] = 180 240 – 54 000 = 126 240 J	M1	
	[Average resistive force] $F = \frac{126\ 240}{1600}$	M1	M1 : Use of $W = Fd [\cos\theta]$ with $d = 1600$ or 150
	<i>F</i> = 79 N	A1	A1: Correct answer, AWRT 79 N Condone missing units
8(b)(ii)	Air resistance on the cart and driver	E1	Any plausible resistive force
	Friction in the wheel bearings	E1	A second plausible resistive force
	Total	10	

Q	Answer	Marks	Comments
			•
9(a)	[Time taken for the basketball to cover the 4.0 m]		
	$T = \frac{4.0}{9.5\cos(\theta)}$	B1	Any subject
	$[s =]9.5\sin(\theta)T - 0.5 \times 9.8 \times T^2$	M1 A1	M1: Use of $s = ut + \frac{1}{2}at^2$ with $u = 9.5 \sin(\theta)$ and $a = \pm 9.8$ (PI) A1: Correct
	$[s =]9.5\sin(\theta) \times \frac{4.0}{9.5\cos(\theta)}$ $-0.5 \times 9.8 \times \left(\frac{4.0}{9.5\cos(\theta)}\right)^2$	m1	Eliminating T (PI)
	$[s =]4.0\tan(\theta) - \frac{1568}{1805\cos^2(\theta)}$	A1	Correct and second term in $\cos^2 \theta$
	Use of $\sec^2(\theta) \equiv 1 + \tan^2(\theta)$	M1	
	$1.3 = 4.0\tan(\theta) - \frac{1568}{1805}\tan^2(\theta) - \frac{1568}{1805}$	M1	PI. Use of $s = 1.3$ at the hoop. Can be seen at any point in the
	$\left[\frac{1568}{1805}\tan^2(\theta) - 4.0\tan(\theta) + \frac{7829}{3610} = 0\right]$		solution for the mark
	$\tan(\theta) = 0.627758923, 3.976832914$	m1	PI, solving correct quadratic equation to find two values of $tan(\theta)$
	<i>θ</i> = [32.1°], 75.9°	A1	Condone decimal places
	θ = 76°	E1	Rejects lower angle as basketball passes through hoop from above
9(b)	Basketball has zero volume/is assumed to be a particle	E1	Any plausible assumption
	Total	11	