## UNIVERSITY OF CAMBRIDGE INTERNATIONAL EXAMINATIONS

GCE Advanced Subsidiary Level and GCE Advanced Level

## MARK SCHEME for the May/June 2010 question paper for the guidance of teachers

## 9702 PHYSICS

9702/34

Paper 32 (Advanced Practical Skills), maximum raw mark 40

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

• CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the May/June 2010 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



ge 2		Mark Scheme: Teachers' version	Syllabus	Paper
		GCE AS/A LEVEL – May/June 2010	9702	34
		[		
Six	sets of re	· ·	res 4 marks, etc.	I
		alues of $d \ge 15$ cm.		Ī
Eac tab The	ch colum le. ere must	nn heading must contain a quantity and a unit.	_	
	•			
			iven for raw d. Cho	eck each row
			t value.	1
(i)	Axes – Sensible Scales both x a Scales Allow in	must be chosen so that the plotted points occu and y directions. Indicate a false origin with FO. must be labelled with the quantity that is being playerted axes but do not allow the wrong graph.	py at least half the otted. Ignore units	e graph grid
	Tak Six Inc Ra Ra Col Eac tab The 1/d Col All Sig S.f.	Table – Six sets of r Incorrect tre Range – Range of va Column hea Each colum table. There must 1/d (m <sup>-1</sup> ). Consistency All raw valu Significant f S.f. for 1/d r Calculated v Check the s (i) Graph Axes – Sensibl Scales both x a Scales Allow in	Apparatus set up without help from Supervisor.  Value of <i>L</i> to nearest mm.  Table −  Six sets of readings of <i>d</i> and <i>h</i> scores 5 marks, five sets scollicorrect trend −1.  Range −  Range of values of <i>d</i> ≥ 15 cm.  Column headings −  Each column heading must contain a quantity and a unit. table.  There must be some distinguishing mark between the quantity (m <sup>-1</sup> ).  Consistency −  All raw values of <i>h</i> must be given to the nearest mm.  Significant figures −  S.f. for 1/ <i>d</i> must be the same as, or one more than, the s.f. general column and the scales of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong, write in the correct of the specified value of 1/ <i>d</i> . If wrong write in the correct of the specified value of 1/ <i>d</i> . If wrong write in the correct of the specified value of 1/ <i>d</i> . If wrong write in the correct of the specified value of 1/ <i>d</i> . If wrong write in the correct of the specified value of 1/ <i>d</i> . If wrong write in the correct of the specified value of 1/ <i>d</i> . If wrong write in the correct of the specified value of 1/ <i>d</i> . If wrong write in the specified value of 1/ <i>d</i> . If wron	Apparatus set up without help from Supervisor.  Value of <i>L</i> to nearest mm.  Table – Six sets of readings of <i>d</i> and <i>h</i> scores 5 marks, five sets scores 4 marks, etc. Incorrect trend –1.  Range – Range of values of <i>d</i> ≥ 15 cm.  Column headings – Each column heading must contain a quantity and a unit. Ignore units in thable.  There must be some distinguishing mark between the quantity and the unit e 1/ <i>d</i> (m <sup>-1</sup> ).  Consistency – All raw values of <i>h</i> must be given to the nearest mm.  Significant figures – S.f. for 1/ <i>d</i> must be the same as, or one more than, the s.f. given for raw <i>d</i> . Check the specified value of 1/ <i>d</i> . If wrong, write in the correct value.  (i) Graph Axes – Sensible scales must be used. Awkward scales (e.g. 3:10) are not allowed Scales must be chosen so that the plotted points occupy at least half the both <i>x</i> and <i>y</i> directions. Indicate a false origin with FO. Scales must be labelled with the quantity that is being plotted. Ignore units

All observations must be plotted.

Do not accept 'blobs' (points > half a small square).

Ring and check a suspect point. Tick if correct. Re-plot if incorrect.

Work to an accuracy of half a small square.

(ii) Line of best fit -

Judge by the balance of at least 5 trend points about the candidate's line. There must be an even distribution of points either side of the line along the whole length.

[1]

[1]

[1]

Indicate best line if candidate's line is not the best line.

Line must not be kinked or thicker than 1 mm.

Quality -

Judge by scatter of all points about a best line. All plots from table (minimum 5) must be within  $0.1 \text{ m}^{-1}$  of a straight line (in 1/d direction).

Do not credit if it is the wrong graph or if the trend is wrong.

	Page 3	Mark Scheme: Teachers' version	Syllabus	Paper
		GCE AS/A LEVEL – May/June 2010	9702	34
	` ,	Gradient – The hypotenuse of the triangle must be at least half the least Read-offs must be accurate to half a small square – if wro Check for $\Delta y/\Delta x$ (i.e. do not allow $\Delta x/\Delta y$ ).  y-intercept – Value must be read from graph to nearest half small so origin) or calculated using ratios or $y = mx + c$ .	ng write in the co	orrect value(s). [1]
	Igno	ect calculation of <i>z</i> (gradient value <u>must</u> be used). re sign. e of <i>z</i> given with unit of length (gradient value <u>must</u> be use	ed).	[1] [1] <b>[Total: 20]</b>
2	(a) Mea	surement of $I$ in range 1.5 A–2.5 A and to 0.1A or better.		[1]
	(c) Mea	surement of x to the nearest mm.		[1]
	(d) Mea degr	surement of $ heta$ (less than 45°). Raw values to no more ee.	e than nearest o	degree or half [1]
	(e) Pero	entage uncertainty in $\theta$ : Correct method, using $\Delta\theta$ = half t	he range, or $\Delta  heta$ =	= 2° to 10°. [1]
	(f) (i)	Evidence of repeated measurements either here or in (d).		[1]
	(ii)	Correct average value of $\theta$ .		[1]
	Seco	and measurement of $x$ .  Find measurement of $I$ .  Find ity: $I$ decreases as $x$ decreases.		[1] [1] [1]
	(ii)	Correct calculation of two values of $k$ .  Valid conclusion based on the calculated values of $k$ . Ospecified criterion.	Candidate must	[1] test against a [1]

(iii) Statement that the s.f. for k depend on the s.f. for I and x. Ignore any reference to d.p. [1]

Page 4	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2010	9702	34

## (i) Identifying limitations and suggesting improvements

	Limitations (4)	Improvements (4)	Ignore
A	Two readings (of <i>x</i> and <i>I</i> ) are not enough (to draw a valid conclusion).	Take more readings <u>and plot a</u> <u>graph</u> .	Repeat readings.
В	Difficult to measure x / difficult to keep x constant / difficult to keep distance between wire and magnet constant / difficult to keep distance between wire and stick constant.	Use a clamped ruler / method of fixing the string	Parallax error in measuring <i>x</i> .
С	Magnet does not come to rest.	Practical method of damping / shield from draughts / turn off fans.	Magnet swings too fast.
D	Measured angles are very small	Use larger currents / use bigger protractor	Use stronger / larger magnet.
E	Parallax error in measuring $\theta$ / reading protractor / reading deflection.	Method of bringing protractor closer to wire / shine light from above	Increase x / use mirror.
F	Difficult to alter rheostat while holding string.	Method of fixing the string (unless already credited in B) / method of fixing rheostat to bench / use assistant.	
G	$(\theta  \text{affected by})  \text{magnetic}$ materials nearby / stray magnetic fields.	Use wooden / non-magnetic stands.	Move object further away.
Н	Fluctuating current.	Method of improving contact with wire (e.g. cleaning contacts, soldered connections).	

Do NOT credit: Use sensors / use lightgates / use video.

[Total: 20]